

FITTING INSTRUCTIONS: ROLLER BLIND WITH CASSETTE & TRACKS



pic 1



pic 2



pic 3



pic 4



pic 5

PARTS INCLUDED (pic 1)

- 1 x cassette and roller blind
- 2 x track with end caps
- cassette brackets (min. 2 cassette brackets supplied; 3 or more supplied for widths over 100cm)
- screw pack (as requested)

HOW TO FIT:

1. MARK THE BRACKET POSITIONS

- Measure 6.5cm from the back of the window recess and draw a straight line along the length of the window recess in pencil. If you have window handles that protrude into the window recess, ensure you measure 6.5cm from the window handles. (pic 2)
- Space the brackets evenly along the line you have just drawn. Mark the oval screw hole positions using the brackets as a guide. Ensure the bracket release tab is closest to the window. (pic 3)

2. FIT THE BRACKETS (pic 4)

If fitting into masonry, drill the screw hole positions with a 5mm drill bit and fit the plugs provided. If fitting into plasterboard, use the 'driva' heavy duty plasterboard fixings at the screw hole positions.

- Secure the brackets into position using the screws provided.

3. FIT THE CASSETTE (pic 5)

Clip the cassette to the brackets, hooking into the front of the brackets first and then into the back of the brackets until the cassette 'clicks' into place. Push the bracket release tabs to release the cassette if necessary.



pic 6



pic 7



pic 8



pic 9

4. FIT THE SIDETRACKS (pic 6)

- a. Position the tracks with the curved end caps under the cassette, ensuring the tracks are straight and level. We recommend using a spirit level to help ensure the tracks are straight.
- b. Mark the screw hole positions wall with a pencil through the pre-drilled holes. (pic 7)
- c. Ensure the bottom bar of the roller blind is positioned inside the track before securing the track in place with the screws provided. (pic 8)

- b. Fit the safety link by pushing each end of the chain into the ball shaped cut-outs in the device. Test the device by pulling hard on the chain either side of the device - the device should break apart!

5. FIT THE CHILD SAFETY DEVICES

By law, blinds which have their chain control loop at less than 150cm from the floor must be fitted with at least one child safety device. We supply you with two different devices - a chain tidy and a chain control safety link. You may choose to fit just one or both of them.

CHAIN CONTROL SAFETY LINK (pic 9)

The chain control safety link is designed to break apart if excessive force is applied, thereby reducing the risk of strangulation.

- a. Remove the standard metal link by squeezing the chain together so that it levers out of the slots in the link.



pic 10



pic 11



pic 12

CHAIN TIDY DEVICE

The chain tidy device is supplied as either a 'face fix' (pic 10) or 'recess fix' (pic 11) as requested. The face fix device fixes to the wall or window frame and extends out. The recess fix device fixes to the side of the window recess. The chain threads through this device to eliminate a free-hanging loop, thereby reducing the risk of strangulation.

- a. Thread the chain control through the opening slot in the device.
- b. Position the device so that the chain is held reasonably taut, but with enough slack to allow the metal link or safety link to pass through. Mark the screw hole positions.
- c. Secure the device using the screws provided.

6. FIT THE POSITION STOP DEVICE

The position stop device clips onto the control chain to prevent the blind from being lowered too far.

- a. Lower the blind to its precise fully down position.
- b. Note the point on the chain just where it disappears into the mechanism. This is the point where the device is to be fitted.
- c. Push the device onto the chain using firm pressure. (pic 12)

OPERATION

Gently pull on the chain control to raise and lower your blind.

CARE INSTRUCTIONS

Wipe clean with a damp cloth.

SAFETY WARNING

Chain controls should be kept out of reach of children. Move cots and furniture away from the blind's chain controls.



Love your blinds? Send us some photos or post them on social media - we'd love to see them! Don't forget to tag us @TheBlindShop.